



Combi-15-Axon

2 x Axon-12x3

2 x Ventus-15

Amplifier recommendation:

Powersoft T604, 4 x 1.250 W/8 Ω, 4 x 1.500 W/4 Ω

Combi-15sp-Axon

2 x Axon-12x3

1 x Ventus-15

1 x Ventus-15sp

Axon-12x3

Frequency range	100 Hz - 16 kHz (- 10 dB) 140 Hz - 14 kHz (+/- 3 dB)
Coverage range	80° x 20°
Power handling	240 W AES / 480 W program / 960 W peak at 12 Ω
Sound pressure	119 dB SPL AES / 122 dB SPL program / 125 dB SPL peak
Components	12 x 3" Wideband transducer
Connectors	2 x Neutrik NL4 Speakon IN/OUT (loop through), configuration: 1+/1-
Dimensions	1.034,5 (h) x 115 (w) x 145 mm (d)

Ventus-15/15sp

Lower cut-off frequency	34 Hz (- 10 dB) 43 Hz (+/- 3 dB)
Power handling	1.000 W AES / 2.000 W program / 4.000 W peak at 8 Ω
Sound pressure	127 dB SPL AES / 130 dB SPL program / 133 dB SPL peak
Components	1 x 15" Woofer with 4" voice coil
Connectors	2 x Neutrik NL4 Speakon IN/OUT (loop through), configuration: 2+/2-
Dimensions	438 (h) x 580 (w) x 540 mm (d)
Amplifier	4.6 kW, three channels
Power output CH1	2.600 W/ 8 Ω, 2.200 W/ 4 Ω
Power output CH2 & CH3	750 W/ 8 Ω, 1.000 W/ 4 Ω, 750 W/ 2 Ω

